HellermannTyton

Article Number: 380-03005



Description: Heat Shrink Tubing, 3:1 Assorted Universal Kit, assorted Dia, color & lengths, PO, Assorted Colors, 177 pcs/pkg

| Base Data | | |
|-----------------------------|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | | |
| | Local Order Number | 380-03005 |
| | Туре | ShrinKit 321 Universal Basic |
| | Color | Black (BK) |
| | Features and benefits | The assorted universal kit contains 177 pieces of assorted color polyolefin heat shrink tubing invarious diameter sizes and lengths. The 3 to 1 shrink ratio covers a wide range of components, sizes and shapes. Material is self-extinguishing, for use in applications in which non- flammable materials are required. |
| | Quantity Per | kit |
| | Product Description | Heat shrink kits are a convenient solution for "on-the-job" projects. This 3 to 1 shrink ratio tubing features a flexible, thin wall to cover a wide range of components, sizes and shapes. The polyolefin material has a higher operating temperature range than general-use heat shrink tubing. Theassorted universal kit contains an assortment of colored tubing in variety of diameter sizes and lengths. |
| | Short Description | Heat Shrink Tubing, 3:1 Assorted Universal Kit, assorted Dia, color & lengths, PO, Assorted Colors, 177 pcs/pkg |
| Product Dimensions | | |
| | Printable (Yes/No) | No |
| | Shrink Ratio | 3:1 |
| | Variant | Thin-Wall |
| Material and Specifications | | |
| | Material | Polyolefin, cross-linked (PO-X) |
| | Material Shortcut | PO-X |
| | Dielectric Strength (Metric) | 20 kV/mm according to ASTM D 2671 |
| | Elongation at break | 600% |
| | Flammability | self-extinguishing |
| | Shrink Temperature | +194 °F (+90 °C) |
| | Operating Temperature | -67°F to +275°F (-55°C to +135°C) |

380-03005

HellermannTyton

| Material and Specifications | REACH Compliant (Article 33) | Yes |
|--------------------------------|------------------------------|---------------------------------|
| | ROHS Compliant | Yes |
| | Certification/Specification | SAE - AMS - DTL-23053/5 Class 1 |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 1 |
| | Package Quantity (Metric) | 1 |
| | Customs Number(Schedule B) | 3926909987 |
| | Content Unit (BMEcat) | pieces |
| | Weight (Metric) | 0.16kg |