## **HellermannTyton**

Article Number: 300-73610



Description: Heat Shrink Tubing, 2:1 Shrink Ratio, 1.5", 38.1/19.1 Dia, PO, Black, 100 ft/reel

Base Data		
	Local Order Number	300-73610
	Туре	TCN20-38.1/19.1
	Color	Black (BK)
	Features and Benefits	<ul> <li>Tubing is 2:1, thin wall and self extinguishing providing good resistance to common fluids and solvents.</li> <li>Low shrink temperature gives excellent physical and electrical performance.</li> <li>Available in multiple diameters and lengths offering several options to fit specific needs.</li> </ul>
	Quantity Per	box
	Product Description	TCN20 Heat Shrink is a general purpose, thin wall tubing used to protect electrical and mechanical wiring. Polyolefin material is self extinguishing and resistant against common fluids and solvents. The low shrink temperature and mechanical strength make this tubing widely used in the electric and electronics industry. Available in a wide range of diameters up to 2.0 (50.8mm) and multiple lengths. TCN20 Heat Shrink is UL224 125 °C 600V VW-1 and RoHS.
	Short Description	Heat Shrink Tubing, 2:1 Shrink Ratio, 1.5", 38.1/19.1 Dia, PO, Black, 100 ft/reel
Product Dimensions		
	Length L (Imperial)	100.0ft
	Length L (Metric)	30.5m
	Printable (Yes/No)	Yes
	Shrink Ratio	2:1
	Trade Size	1-1/4 "
	Variant	Thin-Wall
	Volume Resistance (Ohm cm)	10 <sup>14</sup> Ω cm
	Nominal Diameter (Imperial)	1-1/2"
	Nominal Diameter (Metric)	38.1mm
	Wall Thickness WT (Metric)	1.02mm
	Recovered Diameter d (metric)	19.1mm
	Recovered Diameter d (imperial)	0.75"

## 300-73610

## **HellermannTyton**

Product Dimensions	Supplied Diameter D (imperial)	1.5"
	Supplied Diameter D (metric)	38.1mm
Material and Specifications		
	Material	Polyolefin, cross-linked (PO-X)
	Material Shortcut	PO-X
	Dielectric Strength (Metric)	20 kV/mm according to IEC 243
	Elongation at break	400%
	Flammability	self-extinguishing
	Halogenfree	No
	Shrink Temperature	+212 °F (+100 °C)
	Operating Temperature	-67°F to +257°F (-55°C to +125°C)
	ROHS Compliant	Yes
	Certification/Specification	CSA
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	100ft
	Package Quantity (Metric)	30m
	Customs Number(Schedule B)	3926909987