



RECEPTACLE, 4 PIN, REDUCED DIA WIRE SEAL, ATP SERIES


ATP04-4P-RD01XX

<u>ک</u>









NOTES: UNLESS OTHERWISE SPECIFIED


MATERIAL:

HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

- 2. MODIFICATIONS: REDUCED DIAMETER WIRE SEAL
- 3. SPECIFICATIONS:
  - 3.1 CURRENT RATING: 25 AMPS
  - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
  - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC. 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.

  - 3.5 MOISTURE RESISTANCE: IP67 (MATED CONDITION)
  - 3.6 MATING CYCLE DURABILITY: 100 CYCLES
  - 3.7 RoHS COMPLIANT
- 4. MATING PART: ATP06-4S\* PLUG. ( \* = MODIFICATIONS AND COLORS )
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.
- 6 CONTACT SIZE AND REAR SEAL WIRE RANGE:

CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL
SIZE	O.D.	O.D.	WIRE RANGE
12	12 2.46 mm (.097 in)		12 - 14 AWG



PART NUMBER CHART				
COLOR	PART NUMBER			
GREY	ATP04-4P-RD01			
BLACK	ATP04-4P-RD01BK			

STANDARD MOLDED COLOR IS GREY. ADDITIONAL COLOR (BLACK) IS AVAILABLE VIA SPECIAL ORDER. REFER TO PART NUMBER CHART FOR **AVAILABLE CONNECTOR COLORS** 

	SEE PART NUMBER CHART								
	PART N	IUMBER		DESCRIPTION			ITEM		
QUANTITY	MATERIALS LIST								-
UNLESS OTHERWISE SPECIFIED  1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30   Fractions +1/64		SIGNATUR	ES E	DATE	Amphanal				
		DRAWN: JARRY	18	3/OCT/13	Amphenol				
	Angles ±1°	CHECKED:				Sin	ne Systems - www.amphe	nol-sine.com	
3) Note reference =  \( \int \text{X} \)  MATERIAL SPECIFICATIONS:  PROCESS SPECIFICATIONS:		ENGINEER:			44724 Morley Drive				
		APPROVAL:					Clinton Township, MI 48	036	
		CUSTOMER:			RECEPTACLE, 4 PIN, REDUCED				
		SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL		DIAMETER WIRE SEAL, ATP SERIES				5	
				B	C-	ATP04-4P-F	RD01XX	A3	
NEXT ASS'Y:		MANUFACTURING VARIATIONS.		SCALE:	IONE		SHEET 1 OF	1	