## **HellermannTyton**

Article Number: 151-00322

Description: Adhesive Base, 1.12" x 1.12", .18" Max Tie Width, .18" Hole Dia, PA66/Acrylate, White, 500/pkg



Base Data		
	Local Order Number	MB4A10A2H4
	Туре	MB4A
	Color	White (WH)
	Features and Benefits	<ul> <li>For use with 18 and 30 pound cable ties to provide stability when securing bundles.</li> <li>Secures with rubber based adhesive backing and/or two or four screws.</li> <li>4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.</li> </ul>
	Quantity Per	bag
	Product Description	HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.
	Short Description	Adhesive Base, 1.12" x 1.12", .18" Max Tie Width, .18" Hole Dia, PA66/Acrylate, White, 500/pkg
Product Dimensions		
	Length L (Imperial)	1.12"
	Length L (Metric)	28.5mm
	Fixation Method	Screw Mounting and Adhesive
	Width W (Imperial)	1.12"
	Width W (Metric)	28.5mm
	Cable Tie Width Max. (Imperial)	0.18"
	Cable Tie Width Max. (Metric)	4.6mm
	Height H (Imperial)	0.23"
	Height H (Metric)	5.8mm
	Mounting Hole Diameter D (Imperial)	0.18"
	Mounting Hole Diameter D (Metric)	4.6 mm
	Mounting Hole Centers (Imperial)	0.8"

## 151-00322

## **HellermannTyton**

Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Adhesive	Acrylate with base of acrylic foam
	Flammability	UL 94 V2 (excluding adhesive)
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	ROHS Compliant	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500
	Customs Number(Schedule B)	3926909987